

SAFE LUBE™

Industrial Lubricants & Metalworking Fluids



SAFE LUBE™ GEAR LUBE ISO 90 & 150

DESCRIPTION: **SAFE LUBE™ Gear Lube** is a leading edge technology, combining the advantages of a blended vegetable oil base with an extreme pressure performance package compounded from botanical sources. **SL-Gear Lube** contains a unique blend of environmentally acceptable corrosion inhibitors, thickeners and wear-reducers. The proper AGMA grade is ideal for all types of gear units in a variety of services and environments and provides superior protection from heat and wear. **SL-Gear Lube** is designed for use in industrial power transmission units and gearboxes. It can also be used as a general high-viscosity industrial oil for sprockets, ways and chains. **SL-Gear Lube** offers cooler, more efficient running and significant savings minimizing friction and wear. **SL-Gear Lubes** can be applied in gearboxes as you would conventional gear oils or as GP oil. Use wipe or brush methods, submersion bath, drip or pressure applicators and sprayers.

PROPERTIES:	Viscosity (40°F)	Varies
	Color	Light to Dark Brown
	Specific Gravity (Water=1.0)	0.95+/-0.05
	Flow Point/Pour Point	<5°F (-15°C)
	Flash Point (COC)	>500°F

ADVANTAGES:

- Botanical EP package reduces sliding, rolling & pressure friction
- Lower operating temperatures and prolonged fluid life
- Improves heat transfer from gears to exterior of gear box
- Non-foaming, water repelling, rust preventive
- Environmentally safe - biodegradable (US EPA 560/6-82-003)
- Used vegetable oil products are not hazardous, reducing disposal cost
- Safe for workers – non-reactive and non-irritating to skin and lungs
- Unregulated product- not reported under SARA, TSCA or RCRA

SAFE LUBE™ PRODUCTS ARE:

- Non-toxic
- Non-reactive
- Non-carcinogenic
- Readily biodegradable
- Derived from renewable resources
- Safe to use, store and dispose of

SAFE LUBE™ PRODUCTS DO NOT CONTAIN:

- Petroleum distillates
- Sulfur
- Chlorine
- Synthetics
- Heavy Metals

The information contained herein is believed to be correct including test data conducted under controlled laboratory conditions. Users of **SAFE LUBE** products should perform their own test(s) to determine the suitability of the product for their specific application(s). For questions: techsupport@gemtek.com

A Division of **GEMTEK® Products**

3808 North 28th Avenue • Phoenix, AZ 85017 • 602-265-8586 • FAX 602-265-7241 • www.gemtek.com