

SAFE LUBE™

Industrial Lubricants & Metalworking Fluids



SAFE LUBE™ WAY LUBES ISO 32, 46 & 68

DESCRIPTION: *SAFE LUBE™ Way Lubes* represent leading edge technology combining the advantage of blended vegetable oil bases with extreme pressure additive in a botanical format. All **SL-Way Lubes** exhibit high “load carrying” film formation to protect the ways during the most severe application. The botanical films maintained by the **SL-Way Lubes** are water resistant and therefore resist “coolant washout” for longevity of the ways. **SL-Way Lubes** are applied to opposing metal glide surfaces or tracks in order to improve lubricity, reduce galling and protect against the corrosive effects of cutting fluids. **SL-Way Lubes** may be applied using spray, wipe or brush methods.

PROPERTIES:	Viscosity (40°C)	ISO Grades 32, 46 & 68
	Color	Dark Amber
	Specific Gravity (Water=1.0)	0.90+/- 0.96
	Flow Point/Pour Point	NA
	Flash Point (COC)	>400°F

ADVANTAGES:

- Botanical EP package reduces sliding & pressure friction
- Prevents wear between close tolerance parts
- Resists wash off with coolant oils
- Used oil is not hazardous; reducing disposal costs
- Environmentally safe – Complies with USEPA 560/6-82-003
- Safe for workers – non-reactive and non-irritating to skin and lungs

SAFE LUBE™ PRODUCTS ARE:

- Non-toxic
- Non-reactive
- Non-carcinogenic
- Readily biodegradable
- Derived from renewable resources
- Safe to use, store and dispose of

SAFE LUBE™ PRODUCTS DO NOT CONTAIN:

- Petroleum distillates
- Sulfur
- Chlorine
- Synthetics
- Heavy Metals

The information contained herein is believed to be correct including test data conducted under controlled laboratory conditions. Users of **SAFE LUBE** products should perform their own test(s) to determine the suitability of the product for their specific application(s). For questions: techsupport@gemtek.com

A Division of **GEMTEK® Products**

3808 North 28th Avenue • Phoenix, AZ 85017 • 602-265-8586 • FAX 602-265-7241 • www.gemtek.com