

SAFE LUBE™

Industrial Lubricants & Metalworking Fluids



SAFE LUBE™ WIRE ROPE LUBE - Film Forming

DESCRIPTION: *SAFE LUBE™ Wire Rope Lube - Film Forming* is non-toxic and biodegradable. It incorporates leading edge technology, combining the advantages of a vegetable oil base with wear-reducers compounded from botanical sources. It is ideal for manual application to all types of wire ropes and chains in a variety of services and environments. *SL-Wire Rope Lube - Film Forming* covers and penetrates like oil and forms a film to stick like grease, thus increasing protection and wire rope life.

PROPERTIES:	SSU Viscosity @ 100°F	140 - 170
	Color	Bright & Clear Light Yellow
	Specific Gravity (Water=1.0)	0.92+/-0.05
	Flow Point/Pour Point	<5°F (-15°C)
	Flash Point (COC)	>500°F (>260°C)

APPLICATION: *SL-Wire Rope Lube - Film Forming* can be sprayed, wiped, dipped or brushed on, as well as applied with low viscosity core lubricators. Apply as necessary for lubrication and corrosion protection.

ADVANTAGES:

- Aquatically non-toxic, ideal for over water applications
- Environmentally safe – Complies with USEPA 560/6-82-003 for biodegradation
- Penetrates like an oil; sticks like a grease
- Protects wire ropes, cables and chains from wear and corrosion
- Extended equipment life; no rusting or smoking
- Used lube (botanical) is not hazardous – reducing disposal costs
- Safe for workers – non-reactive and non-irritating to skin and lungs
- Unregulated product - not reported under SARA, TSCA or RCRA

SAFE LUBE™ PRODUCTS ARE:

- Non-toxic
- Non-reactive
- Non-carcinogenic
- Readily biodegradable
- Derived from renewable resources
- Safe to use, store and dispose of

SAFE LUBE™ PRODUCTS DO NOT CONTAIN:

- Petroleum distillates
- Sulfur
- Chlorine
- Synthetics
- Heavy Metals

The information contained herein is believed to be correct including test data conducted under controlled laboratory conditions. Users of **SAFE LUBE** products should perform their own test(s) to determine the suitability of the product for their specific application(s). For questions: techsupport@gemtek.com

A Division of **GEMTEK® Products**

3808 North 28th Avenue • Phoenix, AZ 85017 • 602-265-8586 • FAX 602-265-7241 • www.gemtek.com