

# SAFE LUBE™

Industrial Lubricants & Metalworking Fluids



## SAFE LUBE™ WIRE ROPE LUBE - Non-Drying

**DESCRIPTION:** *SAFE LUBE™ Wire Rope Lube – Non-Drying* is non-toxic and biodegradable. It is designed for automatic application to all types of wire ropes and chains in a variety of services and environments. It incorporates leading edge technology, combining the advantages of a vegetable oil base with wear reducers compounded from botanical sources. *SL-Wire Rope Lube – Non-Drying* covers and penetrates like oil and remains in a fluid form, thus increasing protection and wire rope life.

<b>PROPERTIES:</b>	<b>SSU Viscosity @ 100°F</b>	170 - 200
	<b>Color</b>	Bright & Clear Straw Yellow
	<b>Specific Gravity (Water=1.0)</b>	0.93+/-0.05
	<b>Flow Point/Pour Point</b>	<5°F (-15°C)
	<b>Flash Point (COC)</b>	>500°F (>260°C)

**APPLICATION:** *SL-Wire Rope Lube – Non-Drying* can be sprayed, wiped, dipped or brushed on, as well as applied with low viscosity core lubricators. Apply as necessary for lubrication and corrosion protection.

### ADVANTAGES:

- Aquatically non-toxic, ideal for over water applications
- Environmentally safe – Complies with USEPA 560/6-82-003 for biodegradation
- Penetrates like an oil
- Protects wire ropes, cables and chains from wear and corrosion
- Extended equipment life; no rusting or smoking
- Used lube (botanical) is not hazardous – reducing disposal costs
- Safe for workers – non-reactive and non-irritating to skin and lungs
- Unregulated product - not reported under SARA, TSCA or RCRA

### SAFE LUBE™ PRODUCTS ARE:

- Non-toxic
- Non-reactive
- Non-carcinogenic
- Readily biodegradable
- Derived from renewable resources
- Safe to use, store and dispose of

### SAFE LUBE™ PRODUCTS DO NOT CONTAIN:

- Petroleum distillates
- Sulfur
- Chlorine
- Synthetics
- Heavy Metals

The information contained herein is believed to be correct including test data conducted under controlled laboratory conditions. Users of **SAFE LUBE** products should perform their own test(s) to determine the suitability of the product for their specific application(s). For questions: [techsupport@gemtek.com](mailto:techsupport@gemtek.com)

A Division of **GEMTEK® Products**

3808 North 28<sup>th</sup> Avenue • Phoenix, AZ 85017 • 602-265-8586 • FAX 602-265-7241 • [www.gemtek.com](http://www.gemtek.com)